

FXB EMERGENCY BULKHEAD

IP65 LED Emergency Luminaire

Fox Lux Emergency Bulkheads are ICEL Endorsed and manufactured to provide full compliance to current standards, including BS 60598-2-22 and ISO 7010.

*5 year warranty including battery**



The luminaire can be wired for either maintained or non-maintained operations and has IP65 protection, meaning that it can be used for in indoor or outdoor applications.

Self-test versions can be remote controlled (see REM10) to enable functional and duration tests on demand, check the status of the battery, and programme the automated self-test at the time required.

KEY FEATURES

- 🦊 IP65 self-contained emergency luminaire
- 🦊 IK10 impact rating
- 🦊 Low stand-by power consumption < 0.5W (NM mode)
- 🦊 Self-test versions and remote controls available
- 🦊 Lithium battery
- 🦊 Maintained or non-maintained configurations as standard
- 🦊 Ceiling or recessed mounting
- 🦊 Suitable for indoor or outdoor applications
- 🦊 Adhesive legends included

Self Test Function

- 🦊 30 second functional test carried out automatically once a week
- 🦊 3hr duration test every 52 weeks.
- 🦊 First full duration within the first 4 weeks of the luminaire being connected to power
- 🦊 Optional remote control available (REM10)

Technical data

Input voltage/frequency	220-240V AC 50Hz
Power consumption	M = 3W, NM = 0.5W
LEDs Lifetime (L-70)	50,000h
Lumen output (M and NM)	FXB01 - 170lm FXB02 – 320lm
Discharge duration	3hr
Charge duration	< 24hrs
Battery type	Li-ion 3.6V 2.5Ah
IP rating	IP65
IK rating	IK10
Insulation class	II
Operation temp.	0-40°C
Storage temp.	0-50°C
Housing	Polycarbonate
Diffuser	Polycarbonate
Finish	Matt white body
Dimensions (L x W x D)	341 x 247 x 46 mm
Net weight (kg)	0.5
Box dimensions (L x W x D)mm	355 x 109 x 60mm



Ordering information

Part no.	Description
FXB01/M/3	LED EM bulkhead IP65 170lm 3hr
FXB01S/M/3	LED EM bulkhead IP65 3hr 170lm – self-test
FXB02/M/3	LED EM bulkhead IP65 3hr 320lm
FXB02S/M/3	LED EM bulkhead IP65 3hr 320lm – self-test

©2019 Fox Lux Ltd. E&OE. Product specification may vary without prior notice. *Terms apply. See website for details.